



Bal Seal® spring-energized seals in high temperature adhesive dispensing valves

PN-370-5 (Rev. 01, 10-31-18)

19650 Pauling
Foothill Ranch, CA
USA 92610-2610
t +1 949 460 2100
f +1 949 460 2300

Jollemanhof 16, 5th floor
1019 GW Amsterdam
The Netherlands
t +31 20 638 6523
f +31 20 625 6018

Suite 901, Chinachem
Century Tower
178 Gloucester Road,
Wanchai, Hong Kong
t +852 28681860
f +852 22956753

www.balseal.com




Overview

Many industries use valves to dispense and control the flow of single part adhesives and hot melt fluids. Typically, these applications are extremely harsh on sealing components because of the high temperatures, abrasive media, and high velocities.

Bal Seal Engineering, Inc. has pioneered a line of sealing solutions tailored for hot melt valves. These field-proven solutions provide reliable service over millions of cycles. Made from formulated and blended PTFE or other engineered polymer compounds for optimized performance, these seals incorporate a metal locking ring that is pressed into the housing to maintain secure mounting despite repeated thermal cycling.

The seals also employ a Bal Spring® canted coil spring energizer to maintain a near-constant contact force against the plunger throughout their service life. Bal Seal® spring-energized seals also have proven performance in many other valve types, including gate valves, ball valves, and needle valves.



Operating Parameters

Pressure

To 1,000 psi (70 kg/cm²)

Speed

4 feet per minute (1.22 meters per minute)
at 1,000 cycles per minute

Temperature

To 400 °F (204 °C)

Media


Hot melt adhesive for packaging

Additional

Low frictional forces, variable pressure and temperature endurance

Features

- Bal Seal® K Series with metal locking rings pressed into the housing reduce diametrical seal shrinkage and provide reliable sealing under constant thermal cycling
- The unique seal contact geometry results in excellent sealing performance
- The Bal Spring® canted coil spring energizer provides near-constant force for optimal performance and long seal life; springs are available in many different materials and loads to accommodate good sealing and low frictional drag at various temperatures
- Filled PTFE seal materials with excellent wear resistance and chemical compatibility, as well as other high-temperature engineered polymer compounds to meet long-term application needs



High Temperature Dispensing Valve

The information, descriptions, recommendations and opinions set forth herein are offered solely for your consideration, inquiry, and verification and are not, in part or in whole, to be construed as constituting a warranty, expressed or implied, nor shall they form or be a part of the basis of any bargain with Bal Seal Engineering, Inc.. If any sample or model was shown to or provided by Buyer/User, such sample or model was used merely to illustrate the general description and type of goods. Such use is not to be construed as a warranty that the goods will conform to the sample or model. Furthermore, THE IMPLIED WARRANTY OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE AND ALL OTHER WARRANTIES, IMPLIED OR EXPRESSED, ARE EXCLUDED AND SHALL NOT APPLY. This document provides product options for further investigation by Buyers/Users having technical expertise. The Buyer/User, through its own analysis and testing, is solely responsible for making the final selection of the products and for assuming that all performance, safety and warning requirements for the application are met. It is recommended that Buyers/Users run evaluation testing under actual service conditions to determine whether proposed Bal Seal Engineering products are suitable for the intended purpose. Nothing contained herein or in any of our literature shall be considered a license or recommendation for any use that may infringe patent rights. (LE-17)

©Copyright 2018 Bal Seal Engineering, Inc. U.S.A.